

Product Name: Potassium Permanganate Crystals**Part No / SKU:** RXSOL-60-6109-250**Date of Issue:** October 06, 2026**Document Type:** Material Safety Data Sheet (MSDS)**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Name	Potassium Permanganate
Part Number	RXSOL-60-6109-250

Chemical Formula: KMnO_4 **Company Details:**

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Kolkata, Chennai, Visakhapatnam, Gandhidham, Nairobi

Phone	+91 22 65113333/ 5555 / 9999 / 27815540-42
Fax	+91 22 2781 1318 :::AOH :0091 9821214367
Email	mail@rxmarine.com ; 123@rxmarine.com

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Concentration	CAS Number	EC Number	R Phrases*	Symbols
Potassium Permanganate	99-100%	7722-64-7	231-760-3	50/5	Xn

*See Section 16

3. HAZARDS IDENTIFICATION

Physical hazards	Not Classified
Health hazards	Not Classified
Environmental Hazards	Aquatic Chronic 2 - H411
Potential Acute Health Effects	Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator). Possibly corrosive to eyes and skin. The amount of tissue damage depends on length of contact. Eye contact can result in corneal damage or blindness. Skin contact can produce inflammation and blistering. Inhalation of dust will produce irritation to gastro-intestinal or respiratory tract, characterized by burning, sneezing and coughing. Severe over-exposure can produce lung damage, choking, unconsciousness or death. Prolonged exposure may result in skin burns and ulcerations. Over-exposure by inhalation may cause respiratory irritation.
Potential Chronic Health Effects	CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance may be toxic to kidneys, liver, skin, central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated skin exposure can produce local skin destruction, or dermatitis. Repeated inhalation of dust can produce varying degree of respiratory irritation or lung damage.

4. FIRST AID MEASURES

Contact with skin	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
Contact with eyes	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
General	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Flammability of the Product	:	Non-flammable
Auto-Ignition Temperature	:	Not applicable.
Flash Points	:	Not applicable.
Flammable Limits	:	Not applicable.
Products of Combustion	:	Not applicable.
Fire Hazards in Presence of Various Substances	:	organic materials, metals, combustible materials
Explosion Hazards in Presence of Various Substances	:	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available. Explosive in presence of organic materials, of metals.
Fire Fighting Media and Instructions	:	Not applicable.
Special Remarks on Fire Hazards	:	Spontaneously flammable on contact with ethylene glycol. Potassium Permanganate being conveyed through propylene tube ignited the tube. When solid hydroxylamine is brought into contact with solid potassium permanganate, there is produced immediately a with flame. Potassium permanganate decomposes hydrogen trisulfide so rapidly that sufficient heat is liberated to ignite the trisulfide. When Antimony or arsenic and solid potassium permanganate are ground together, the metals ignite.
Special Remarks on Explosion Hazards	:	Take care in handling as explosions may occur if it is brought in contact with organic or other readily oxidizable substances, either in solution or in dry state. Explosive in contact with sulfuric acid or hydrogen peroxide. Potassium permanganate + acetic acid or acetic anhydride can explode if permanganate is not kept cold. Explosions can occur when permanganates come on contact with benzene, carbon disulfide, diethyl ether, ethyl alcohol, petroleum, or organic matter. Contact with glycerol may produce explosion. Crystals of potassium permanganate explode vigorously when ground with phosphorous. A mixture of .5% potassium permanganate + ammonium nitrate explosive caused an explosion 7 hrs. later. Addition of Potassium permanganate + dimethylformamide to give a 20% solution led to an explosion after 5 min. During a preparation of chlorine by addition of the concentrated acid (Hydrochloric acid) to solid potassium permanganate, a sharp explosion occurred on one occasion.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Wear protective clothing as per section 8.
Environmental Precautions	Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. The product contains substances which are water-soluble and may spread in water systems. The product contains volatile substances which may spread in the atmosphere
Immediate Actions	Shut off source of leak if safe to do so.
Small Spill	Use appropriate tools to put the spilled solid in a convenient waste disposal container.
Large Spill	Oxidizing material. Corrosive solid. Stop leak if without risk. Do not get water inside container. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

7. HANDLING AND STORAGE

Handling	Keep away from heat. Keep away from sources of ignition. Keep away from combustible material. Do not ingest. Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as organic materials, metals, acids.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area. Separate from acids, alkalies, reducing agents and combustibles. See NFPA 43A, Code for the Storage of Liquid and Solid Oxidizers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Control	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.
Personal Protection	Splash goggles. Synthetic apron. Vapor and dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in case of Large Spill	Splash goggles. Full suit. Vapor and dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Exposure Limits	TWA: 5 Consult local authorities for acceptable exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Odour	:	Odourless
Taste	:	Sweetish, astringent.
Appereance	:	Solid/Powder/Crystal
Molecular Weight	:	158.03 g/mole
pH (1% soln/water)	:	Not available
Boiling Point	:	Not available
Melting Point	:	Decomposes.
Critical Temperature	:	Not available.
Specific Gravity	:	2.7 @ 15 C (Water = 1)
Vapor Pressure	:	Not available.
Vapor Density	:	Not available.
Volatility	:	Not available.
Odor Threshold	:	Not available.
Water/Oil Coeff	:	Not available.
Ionicity (in Water):	:	Not available.
Solubility	:	Easily soluble in methanol, acetone. Partially soluble in cold water, hot water. Soluble in Sulfuric Acid

10. STABILITY AND REACTIVITY

Stability	:	The product is stable.
Instability Temperature	:	Not available
Conditions of Instability	:	Incompatible materials
Incompatibility with various substances	:	Highly reactive with organic materials, metals, acids. Reactive with reducing agents, combustible materials.
Corrosivity	:	Not available.
Special Remarks on Reactivity	:	It is a powerful oxidizing agent. Incompatible with reducing agents, acids, formaldehyde, ammonium nitrate, dimethylformamide, glycerol, combustible materials, alcohols, arsenites, bromides, iodides, charcoal, organic substances, ferrous or mercurous salts, hypophosphites, hyposulfites, sulfites, peroxides, oxalates, ethylene glycol, Manganese salts in air oxidize the toxic sulfur dioxide to more toxic sulfur trioxide. Can react violently with most metal powders, ammonia, ammonium salts, phosphorous, many finely divided organic compounds (materials), flammable liquids, acids, sulfur.
Polymerization	:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 1090 mg/kg [Rat]. Lowest Published Lethal Dose: LDL[Woman] - Route: Oral; Dose: 100 mg/kgLDL[Human] - Route: Oral; Dose: 143 mg/kg.
Chronic Effects on Humans	MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. May cause damage to the following organs: kidneys, liver, skin,central nervous system (CNS).
Other Toxic Effects on Humans	Hazardous in case of skin contact (irritant), of eye contact (corrosive), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	May cause adverse reproductive effects (Male and Female fertility) based on animal data. May affect genetic material (mutagenetic) based on animal data.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Not available
Mobility	Completely soluble in water
BOD5 and COD	Not available
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.
Special Remarks on the Products of Biodegradation	Not available

13. DISPOSAL CONSIDERATIONS

Disposal considerations	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
-------------------------	--

14. TRANSPORT INFORMATION

- Not classified as hazardous for transport
- DOT Classification: CLASS 5.1: Oxidizing material.
- Identification: : Potassium permanganate UNNA: 1490 PG: II
- Special Provisions for Transport: Not available.

15. REGULATORY INFORMATION

Federal and State Regulations	Connecticut carcinogen reporting list.: Potassium permanganate Illinois toxic substances disclosure to employee act: Potassium permanganate Illinois chemical safety act: Potassium permanganate New York release reporting list: Potassium permanganate Rhode Island RTK hazardous substances: Potassium permanganate Pennsylvania RTK: Potassium permanganate Massachusetts RTK: Potassium permanganate Massachusetts spill list: Potassium permanganate New Jersey: Potassium permanganate New Jersey spill list: Potassium permanganate Louisiana spill reporting: Potassium permanganate California Director's list of Hazardous Substances: Potassium permanganate
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances. Other Classifications: WHMIS (Canada): CLASS C: Oxidizing material. CLASS E: Corrosive solid. DSCL (EEC): R8- Contact with combustible material may cause fire. R22- Harmful if swallowed. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. S60- This material and its container must be disposed of as hazardous waste. S61- Avoid release to the environment. Refer to special instructions/Safety data sheets.
HMIS (U.S.A.):	Health Hazard: 2 Fire Hazard: 0 Reactivity: 0 Personal Protection: j
National Fire Protection Association	Health: 1 Flammability: 0 Reactivity: 0 Specific hazard: NA
Protective Equipment:	Gloves. Synthetic apron. Vapor and dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

16. OTHER INFORMATION AND DISCLAIMER

*The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall **Rx Marine International** be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if **Rx Marine International** has been advised of the possibility of such damages.*

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.